

This listing of claims will replace all prior versions, and listings of the claims in the application:

Listing of Claims:

Claims 1-22 are pending in the present application.

1. (Currently Amended) A method for suturing tissue in the proximity of an aperture in a tissue wall, comprising:
forming a port [from the proximal side of] within the tissue wall in the proximity of said aperture;
passing at least a portion of a suture from the distal side of the tissue wall proximally through the port in the tissue wall [in the proximity of the aperture]; and
forming a loop with the remaining portion of the suture to secure the suture.
2. (Currently Amended) The method of Claim 1, wherein forming a port comprises:
advancing a needle [from the proximal side to the distal side of the] through the tissue wall to form the port; and
wherein passing at least a portion of a suture comprises:
engaging the suture with the needle; and
withdrawing the needle and suture through the port.
3. (Previously Considered) The method of Claim 1, further comprising:
introducing a fastener over the portions of the suture.
4. (Previously Considered) The method of Claim 1, further comprising:
passing the remaining portion of the suture through the wall graft.
5. (Currently Amended) The method as in Claim 1, wherein passing at least a portion of a suture comprises advancing a shaft through the aperture so that a pair of needles having a length of suture therebetween engage suture ports on opposite sides of the aperture, drawing the suture outwardly to guide the needles through the suture ports into the tissue tract, and removing the ends of the suture from the needles.
6. (Currently Amended) The method as in Claim 1, wherein passing at least a portion of a suture comprises advancing a shaft through the aperture so that at least one needle having a portion of suture engages the port, engaging the suture portion with the needle, drawing the suture portion through the tissue and retracting the needle from the port.
7. (Currently Amended) The method as in Claim 1, further comprising:
passing the remaining portion of suture through the aperture before the step of passing the suture portion through the tissue wall.

8. (Currently Amended) A method for suturing an aperture in a vessel wall, comprising:
[reversibly] advancing a plurality of needles through the vessel wall to form ports in the proximity of the aperture;
passing at least a portion of a suture proximally through the ports in the vessel wall disposed on opposite sides of the aperture from the interior of the vessel with the remaining portion of the suture passing out of the vessel; and
securing the ends of the suture to close the aperture.
9. (Previously Considered) The method as in Claim 8, further comprising:
passing the suture portion through the ports as a continuous loop with two ends.
10. (Previously Considered) The method as in Claim 8, further comprising:
passing the suture portion through the ports by passing at least a portion of a pair of needles therethrough while carrying the suture portion therebetween.
11. (Previously Considered) The method as in Claim 10, further comprising:
Carrying the suture portion between the pair of needles as a continuous length.
12. (Previously Considered) The method as in Claim 8, further comprising:
Passing the needles from the exterior of the vessel, through the ports in the vascular tissue, and external the vessel so that at least a portion of the suture is external to the vessel.
13. (Previously Considered) The method as in Claim 8, further comprising:
Removing the suture portion from the needles after removing the needles from the vessel.
14. (Previously Considered) The method as in Claim 8, wherein the portions of the suture are secured over the wall of the vessel to close and aperture.
15. (Previously Considered) The method as in Claim 8, wherein the portions of the suture are secured to contact the vessel wall with a graft in an anastomosis.
16. (Previously Considered) A method of suturing an opening in a vessel wall, comprising:
positioning opposite ends of a length of suture within the vessel;
puncturing holes through the vessel wall with a pair of needles;
pulling the opposite ends of the length of suture through the vessel wall, wherein each needle pulls an end of the length of suture in a proximal direction through the holes in the vessel wall.

17. (Previously Considered) The method of Claim 16, further comprising:
tying the opposite ends of the length of suture to close an opening in the vessel wall.

18. (Previously Considered) The method of Claim 16, wherein the opposite ends of the suture loop are positioned within the vessel by:
supporting the opposite ends of the length of suture on a distal end of an elongated member; and
advancing the elongated member through the opening in the vessel wall such that the distal end of the elongated member is positioned within the vessel.

19. (Previously Considered) The method of Claim 18, wherein each of the pair of needles moves in a path which is radially angled to the elongated member as the needles pass through the vessel wall.

20. (Previously Considered) The method of Claim 18, wherein the ends of the needles move radially outwardly from the elongated member prior to passing through the vessel wall.

21. (Previously Considered) The method of Claim 16, wherein each needle has a barbed tip.

22. (Previously Considered) The method of Claim 16, wherein the holes are disposed longitudinally along the length of the vessel wall.

23. (Previously Considered) The method of Claim 16, wherein the holes are disposed transversely along the width of the vessel wall.

24. (New) A method for suturing tissue in the proximity of an aperture in a tissue wall, comprising:
advancing a suturing device having a distal end and a flexible sheath extending therefrom through the aperture in the tissue wall;
passing at least a portion of a suture from the distal side of the tissue wall; and
forming a loop with the remaining portion of the suture to secure the suture.